

## Safety Data Sheets (SDSs)

Product Name: Lithium-ion Battery System

Commissioner: Hiconics Eco-energy Drive Technology Co., Ltd.

# Safety Data Sheets (SDSs)

Name of Product	Lithium-ion Battery Pack
Type/Model	MD-BS5.0-HSST , MD-BS10.0-HSST , MD-BS15.0-HSST MD-BS20.0-HSST , MD-BS30.0-HSST
Commissioned by	Hiconics Eco-energy Drive Technology Co., Ltd.
Commissioner address	No.3 Boxing 2nd Road, Economic and Technological Development Zone, 100176 Beijing, P.R China
Supplier	Hiconics Eco-energy Drive Technology Co., Ltd.
Supplier address	No.3 Boxing 2nd Road, Economic and Technological Development Zone, 100176 Beijing, P.R China
Inspection according to	GLOBALY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS, Rev.11)
Emergency telephone number	+61 1800 511 806
Remarks	/
Date of issue: 2025-12-29	

# Safety Data Sheets (SDSs)

## SECTION 1: Product and company identification

### Product Identifier:

Product name: Lithium-ion Battery System

Model: MD-BS5.0-HSST , MD-BS10.0-HSST , MD-BS15.0-HSST

MD-BS20.0-HSST , MD-BS30.0-HSST

### Other means of identification:

Synonyms: None

### Relevant identified use of Product and uses advised against:

Recommended Use: -

Uses advised against: -

### Details of the Supplier of the safety data sheet:

Name: Hiconics Eco-energy Drive Technology Co., Ltd.

Address: No.3 Boxing 2nd Road, Economic and Technological Development Zone,  
100176 Beijing, P.R China

Telephone: +86 10 5918 0033

E-mail address: hiconics\_service@midea.com

### Emergency telephone number:

Company Emergency Phone Number:+61 1800 511 806

### Imported merchants :

Name:Midea ElectronicsAustralia Co Pty Ltd

Address:Suite Level 12, 600 St Kilda Road Melbourne VIC 3004,Australia

Telephone: +61 1800 511 806

E-mail address:Cheng4.Wang@midea.com

## SECTION 2: Hazard identification

### Classification:

The watt-hour rate of the product is 5.1kWh, it is belong to the class 9 dangerous goods.

The product is tested according to Section 38.3 of the Manual of Tests and Criteria, the test report number is: RZUN012025-1015-M1.

### Other information

Caution! Avoid short circuit place in high temperature environment, put into water, or damage the shell.

## SECTION 3: Composition/information on ingredients

### Chemical characterization: Mixtures

Description: Chemical power supply based on nonaqueous electrolyte. Composed by positive electrode, negative electrode, diaphragm, electrolyte and shell.

Hazardous ingredients:

Common Chemical Name	Chemical Formula	Concentration (%)	CAS No.	EC No.
Aluminum Foil	Al	3.5	7429-90-5	231-072-3
Copper Foil	Cu	7.8	7440-50-8	231-159-6

# Safety Data Sheets (SDSs)

Lithium Iron Phosphate	LiFePO <sub>4</sub>	34.1	15365-14-7	604-917-2
Carbon (proprietary)	C	16.7	7782-42-5	231-955-3
Separator (proprietary)	(C <sub>3</sub> H <sub>6</sub> ) <sub>n</sub>	3	9003-07-0	-
Electrolyte (proprietary)	LiPF <sub>6</sub> /EC+DEC	20.3	/	-
Aluminum Alloy	Al	14.6	7429-90-5	-

Note: N/A=Not apply.

## SECTION 4: First-aid measures

### First aid measures:

Eye Contact: Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact: Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation: Move to fresh air. If symptoms persist, call a physician.

Ingestion: Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Swallowing: Do not induce vomiting. Get medical attention.

### Most Important Symptoms/Effects:

No information available.

### Indication of any immediate medical attention and special treatment needed:

Inform physician. Treat symptomatically.

## SECTION 5: Fire-fighting measures

### Suitable Extinguishing Media:

CO<sub>2</sub>, dry chemical powder, wet sand, plenty of water (for cooling).

Unsuitable Extinguishing Media: No information available.

### Protective Equipment and Precautions for Firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

### Special hazards arising from the substance or mixture:

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium batteries contain flammable ingredients that may vent, ignite and produce sparks when subjected to high temperature (>150°C), When damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

## SECTION 6: Accidental release measures

### **Personal precautions, protective equipment and emergency procedures:**

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

### **Environmental precautions:**

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

### **Methods and material for containment and cleaning up:**

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non-combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

## SECTION 7: Handling and storage

### **Precautions for safe handling:**

Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Avoid mechanical or electrical abuse.

More than a momentary short circuit will generally reduce the battery service life. Avoid reversing battery polarity within the battery assembly. In case of a battery unintentionally be crushed, rubber gloves must be used to handle all battery components. Avoid contact with eyes, skin. Avoid inhalation. No smoking at working site. Materials to Avoid: Strong oxidizing agents, Corrosives.

### **Conditions for safe storage, including any incompatibilities:**

Store in a cool, well-ventilated area. Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short-circuits. Materials to Avoid: Strong oxidizing agents, Corrosives.

## SECTION 8: Exposure controls/personal protection

### **Engineering Controls:**

Use ventilation equipment if available. Safety shower and eye bath.

### **Personal Protective Equipment:**

Respiratory System: Not necessary under conditions of normal use.

Eyes: Not necessary under conditions of normal use.

# Safety Data Sheets (SDSs)

Clothing: Wear appropriate protective clothing.

Hand: Safety gloves.

**Other Protect:**

No smoking, drinking and eating at working site. Wash thoroughly after handling.

## SECTION 9: Physical and chemical properties

Physical State	Form: Prismatic
	Color: White
	Odour: Odourless
	Odor Threshold: No information available
Change in condition:	
pH, with indication of the concentration	Not determined.
Melting point/freezing point	Not determined.
Initial boiling point and Boiling range:	Not determined.
Flash Point	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Auto-ignition temperature	Product is not self-igniting.
Decomposition temperature	Not determined.
Other Information	No further relevant information available.

## SECTION 10: Stability and reactivity

**Reactivity:** Stable under recommended storage and handling conditions (see section 7).

**Chemical stability:** Stable under normal conditions of use, storage and transport.

**Thermal decomposition/conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of Hazardous Reactions:** None under normal processing.

**Hazardous Polymerization:** Hazardous polymerization does not occur.

**Conditions to avoid:** Strong heating, fire, Incompatible materials.

**Incompatible materials:** Strong oxidizing agents. Strong acids.

**Hazardous Decomposition Products:** Carbon oxides, other irritating and toxic gases.

## SECTION 11: Toxicological information

# Safety Data Sheets (SDSs)

Ref. No.: RZUN012025-8012-DS2

Page 7 of 8 Pages

**Acute toxicity:** No data available.

**Skin corrosion/irritation:** No irritant effect.

**Serious eye damage/irritation:** Cause serious eye irritation.

**Respiratory or skin sensitization:** No sensitizing effects known.

**Specific target organ system toxicity:** No information available.

*Note: The internal battery materials may cause irritation to eyes and skin.*

## SECTION 12: Ecological information

**Toxicity:** No further relevant information available.

**Persistence and degradability:** No further relevant information available.

**Bioaccumulative potential:** No further relevant information available.

**Mobility in soil:** No further relevant information available.

**Results of PBT and vPvB assessment:**

PBT: Not applicable.

vPvB: Not applicable.

**Other adverse effects:** No information available.

## SECTION 13: Disposal considerations

**Waste treatment methods:**

Recommendation: Lithium batteries are best disposed of as a non-hazardous waste when fully or mostly discharged. Contact a licensed professional waste disposal service to dispose of large quantities materials.

**Other disposal recommendations:**

Recommendation: Disposal must be made according to official regulations.

## SECTION 14: Transport information

The product had been tested according to the requirements of the UN manual of tests and Criteria, Part III, subsection 38.3 (see section 2)

**EmS No:** F-A, S-I

**Marine pollutant:** No

**Environmental hazards:** Not applicable.

**Special precautions for user:** Not applicable.

**Proper Shipping name:** Lithium ion batteries

**Hazard Class:** Class 9

**UN/ID Number:** UN3480

**Packaging Group:** II

**Maritime transport:**

# Safety Data Sheets (SDSs)

Page 8 of 8 Pages

**Label for conveyance:** Class 9 Lithium Batteries or Sodium Ion Batteries hazard label  
The goods are complied with the requirements of Packing Instruction P903 of IMDG CODE (Amdt. 42-24) (2024 Edition).

**Land transport:**

**Label for conveyance:** Class 9 Lithium Batteries or Sodium Ion Batteries hazard label  
The goods are complied with the requirements of Packing Instruction P903 of Agreement concerning the International Carriage of Dangerous Goods by Road (ADR 2025).

## SECTION 15: Regulatory information

**International Regulation:**

    GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS)  
    Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations  
    IATA Dangerous Goods Regulations (DGR)  
    INTERNATIONAL MARITIME DANGEROUS GOODS CODE (IMDG CODE)  
    Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)

**EU Regulation:**

    Regulation (EU) 2020/878: Revised Requirements for EU Safety Data Sheets  
    EU regulation (EC) 1272/2008 on "Classification, Labeling and Packaging of Substances and Mixtures" (CLP)  
    Registration, Evaluation and Authorization of Chemicals (REACH)  
    Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)

**US Regulation:**

    American National Standard for Hazardous Workplace Chemicals – Hazard Evaluation and Safety Data Sheet and Precautionary Labeling Preparation  
    US DOT, Code of Federal Regulations, Title 49, Transportation, PT. 100-185

## SECTION 16: Other information

This file is only effective to the batteries(MD-BAT5.0-HSST 102.4V 50Ah 5.1kWh) provided by commissioner Hiconics Eco-energy Drive Technology Co., Ltd.. The commissioner provides the composition information of batteries, and promises its integrity and accuracy. Users should read this file carefully, and use the batteries in correct method. CVC Testing Technology Co., Ltd. (CVC) doesn't assume responsibility for any damage or loss because of misuse of batteries.

---